



<b>Description</b>	<b>Big Cover 1974</b> is a PVC coated Polyester with a PVDF/Acrylic Finish, a choice material for awnings, tents, canopies, gazebos, inflatable structures and light frame supported structures. The material undergoes a lacquering treatment (Rotofluo W) of surface coatings to protect and insulate the PVC layer. Treated with a thin acrylic/fluorinated PVDF blend on one side and an acrylic lacquer coating on the other, Big Cover 1974 provides thermal insulation, sound proofing, superior chemical aging resistance, fire resistance, UV and Gamma radiation stability and exceptional properties in tension and deflection.
<b>Cautions</b>	Never use solvents to clean such as: turpentine, nitre solvents, acetate, aromatic compounds, hydrocarbons (petrol or diesel), acids and caustic products. This may casue corrosion.
<b>Coating</b>	Product has a Polyvinyl Chloride Coating.
<b>Cold Crack</b>	Product Cold Crack is equal to or greater than -30 degrees Celsius (-22 Fahrenheit)
<b>Color Search</b>	18 colors available.
<b>Content</b>	100% Polyvinyl Chloride (PVC)
<b>Description</b>	Vinyl tarpaulin with 100% polyester scrim
<b>Features</b>	Cleaning should be done with soft cloths or soft bristle brushes. Rinse with an abundance of water. The last rinse has to be done with a 2% solution of common sodium hypochlorite diluted in water. Carefully dry entire surface without overheating material. Uses: Awnings, canopies, tents, light structures Finish: PVDF/Acrylic This is a weldable product. Graphics Acceptability: Heat transfer, heat sealed inset fabric, adhesive vinyl, screen printing and hand painting. Adhesion: ASTM F 904 - 16lbs (force/2cm) Product is Rated Ultraviolet Resistant equal to or greater than 1000 hours. The test was done in the XENO machine.
<b>Fire Retardancy</b>	Italy: Class 2, France: M2, Germany: DIN 4102 B1, Scandinavia: SIS 650082, Europe: B s1 d0, USA: CSFM NFPA701. CAN/ULC S109.
<b>Protective Finish</b>	Water Proof
<b>Roll Size</b>	50 yards (45.7 m)
<b>Style</b>	Solids / Plain
<b>Tear Strength</b>	Passes ASTM D2261 - Warp = 50 lbs and Fill = 40 lbs. Passes ASTM D5733 - Warp = 32 lbs and Fill = 30 lbs.
<b>Tensile Strength</b>	Passes ASTM D5034 - Warp = 450 lbs and Fill = 420 lbs. Passes ASTM D5035 (Strip Method) - Warp = 260 lbs Fill = 250 lbs.
<b>Thickness</b>	Product thickness is .5 mm.
<b>Ultraviolet</b>	Product is Rated Ultraviolet Resistant equal to or greater than 1000 hours.
<b>Warranty</b>	10 year limited manufacturer's warranty. 6 year manufacturer's limited warranty when used in rental tents.
<b>Weight</b>	19.00 ounces per square yard.
<b>Width</b>	74" (188.0 cm)

\*\* This information is offered for your general guidance only. It is accurate to the best of our knowledge and is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of this material. Final determination of the suitability of any product for an application rests with the user.

\*This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions. Although we do our best to make sure that the colors on our web site are accurate, actual colors will vary. Subtle color differences and textures may not be fully appreciated on some systems due to differences in monitors and/or printers.