

Recacril® Awning Fabric

Specs, Warranty, Cleaning Guide

| | |
|--------------------------------------|---|
| Specifications Fabric Type | 100% Solution Dyed Acrylic |
| Finish | Flouorocarbon Resin |
| Standard Put Ups | 66 yards / 60 meters |
| Finished Weight / Square Yard | 9 oz / 305 grams / m2 |
| UV Resistance | AATCC-16 Results: 1,500+ hours |
| Abrasion | ASTM-4157 40,000 rubs |
| Hydrostatic | AATCC-127 40 cm |
| Puncture Strength | ASTM-751 38 lbs / 17 kg |
| Tear Strength | ASTM-2261 Warp 11.5 lbs Fill 7.7 lbs |
| Tensile Strength | ASTM D-5034 Grab Warp 287 lbs Fill 149 lbs |
| Shrinkage | Method 5804 100 hours Warp 0.1% Fill 0% |
| General Cleaning Instructions | Proper cleaning and care should be taken to ensure the life of Recacril® fabrics. For regular care and maintenance, excessive dirt should be brushed from the fabric using a soft brush. Fabric should then be sprayed with warm water (not exceeding 100°f/40°c) and air dried. Periodically the fabric should undergo a more thorough cleaning; again brush fabric with a soft bristled brush, spray with warm water, and then apply a gentle non-detergent soap and let stand for 10 to 20 minutes before rinsing. Rinse thoroughly and air-dry. DO NOT USE DETERGENT. |
| Professional Cleaners | When employing professional cleaning service providers, please inquire about the firm's experience working with Recacril® fabrics and their knowledge of cleaning and re-treatment requirements. Do NOT dry clean. |
| Limited 5 Year Warranty | A limited warranty fo five years is guaranteed on S. A. Recasens Recacril products. The warranty protects against the loss of characteristics, rot, mildew and discoloration typical in normal atmospheric conditions. This warranty does not apply against any deterioration of any kind due to abusive use, accidental burns, negligence, vandalism, perforations, natural disasters or act of nature. Normal wear, weather, soiling or stains from environmental pollution or other source are not covered. The product must be properly installed and maintained. The warranty, if applicable, does not cover labor, frames, systems or installation supplied by the dealer. S.A. Recasens makes no fitness of warranty for any particular purposes whatsoever with respect to the goods being sold. No warranties, expressed or implied, extend beyond the description on theface of this agreement. |

PATIO LANE™

**Outdoor
Textiles**

**OUTDOOR
FABRIC CENTRAL**
Exclusively Sunbrella® Products & Sundry Items